## The revolution in processing



## 1953ME-1.8-SET

Content:

1 x syringe

incl. changeable tip "Arrow",

2 x changeable tip and changeable head



1953SP-SCHL Mounting key



1953GK Spare screw head



1953ME-SP Changing head A+B



Changeable tip "Craw"

1953SP2



1953SP3 Changeable tip "Ball"



1953ME-1.8

All displayed products are made of medical stainless steel!



1953SP1

Changeable tip "Arrow"





NEUENKAMPER STR. 80 - 86 · D-42657 SOLINGEN · GERMANY TEL. +49(0)212/81 00 44 · FAX +49(0)212/8 73 45 E-MAIL: INFO@CARLMARTIN.DE · INTERNET: WWW.CARLMARTIN.DE



FINEST DENTAL INSTRUMENTS







By the constant return flow of the remaining anaesthetic of the needle after unscrewing, residues occur in the outlet of the head of the cartridge syringe.

A disinfection in this mostly encapsulated area is practically not workable.

The newly developed, DBGM\* patented cartridge syringe with divisible syringe head enables a perfect processing now. Suitable for thermal disinfection and autoclave (max. 134°C). \*DBGM = German federal utility model

To this you get the following illustrated information.





New syringe head with divisible outlet.

Hygienic processing and each time with new syringe head per patient. (Therefore we recommend to stock a sufficient number of syringe heads.)



Syringe head with fine thread for an easy removal.



Divisible needle outlet.

By this a perfect processing can be effected. Both halfs for the needle outlet are manufactured through computer-controlling (CNC) and marked with A + B each. With several syringes, A + B always match.



The cartridge syringe will be delivered with tip no. 1 as standard.

Tips 1 + 3 are primarily recommended for hole plugs and no. 2 for solid plugs. The syringes and the necessary mounting key can be ordered separately if required.



Changeable tips for the fixation in the cannula plug (solid plug or hole plug)















For dismantling the changeable tip proceed as follows:

- 1. Unscrew the changeable head (pic. 1 + 2)
- 2. Insert the mounting key (pic. 3)
- 3. Unfasten and unscrew the changeable tip (pic. 4)
- 4. Remove the changeable tip from the cartridge holder (pic. 5 7)