

# MidKnight® MK-296 Distinctive, Black Nitrile Exam Glove



# Ergonomically designed with exceptional grip

- Distinctive black color: Hides dirt, stains, oils and grease while making light objects more visible
- Fully textured non-foaming design: For secure grip in dry and wet conditions
- Fentanyl- and gastric acid-tested: For enhanced user protection



#### **Industries**

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Healthcare
- Emergency Medical Services
- Utilities
- Warehousing

#### **Recommended For**

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Use of cleaning tools and robotic equipment
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Blending, compounding solids and liquids
- Raw material sample collection
- Weighing and dispensing of solid and liquid raw materials
- Inspection (picking, checking and marking)
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients





### **TECHNICAL DATA SHEET**

	Product Information	
External Glove Surface	Fully Textured	
Audit Standards	ISO 13485:2003	
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case  Also available in retail packs 10 gloves per pack 50 packs per carton/case	
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country Of Origin	Malaysia	
Product Segmentation	Robust	
Antistatic	Yes	

#### **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	245 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.15 / 6.0		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	24	20	ASTM D412 & D573
Elongation at Break (%)	600	500	ASTM D412
Force at break (N)	7	6	EN 455-2

#### **ORDERING INFORMATION**

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
<b>Product Code</b>	MK-296-XS	MK-296-S	MK-296-M	MK-296-L	MK-296-XL	MK-296-XXL

#### **Performance Standards and Regulatory Compliance**



# For additional information visit us at www.ansell.com, or call us at

## Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

# Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

# Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

### Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

**Ansell**